


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	6 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/8 in.
Stud Size	BLANK TONGUE
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLUE
Panduit Die Index No. on Barrel	P24
Alternate Industry Die Index No. () on Barrel	(7)



RECOGNIZED Wire Connector



REV	DATE	BY	CHK	DESCRIPTION	ECN
02	07/08	JESH	JESH	UPDATED SYSTEM REVISION LEVEL	
01	04/08	JESH	JESH	ADDED CSA AND REMOVED UL FROM STAMP	
00	12/07	JESH	JESH	RELEASED	

PANDUIT CORP. TINLEY PARK, ILLINOIS

LCC6-00-L
Copper Lug - Blank Tongue, Long Barrel

SCALE N/A

DRAWING NO / CAD FILE

LCC6-00-CUST