

# Protective covers - HC-B 16-SD-MLT/FS-AL - 1584525

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Protective cover B16, With single locking latch, protective cover material: Al, height: 20 mm, seal: yes, With lanyard, Diameter of retaining cord eyelet: 30 mm



# **Key Commercial Data**

Packing unit	1 STK
GTIN	4 046356 145190
GTIN	4046356145190
Weight per Piece (excluding packing)	100.180 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

### **Dimensions**

Length	94 mm
Width	43 mm
Height	20 mm
Diameter of retaining cord eyelet	30 mm

### Ambient conditions

Degree of protection	IP66
Ambient temperature (operation)	-40 °C 125 °C

### General

Size	B16
Туре	for sleeve housing without single locking latch



# Protective covers - HC-B 16-SD-MLT/FS-AL - 1584525


### Technical data

# General

Material	Aluminum, die-cast
Seal material	NBR
Locking latch material	High-grade steel, handle: PA-GF
Color	gray
Seal present	yes
Connection	The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts.

# Drawings

### Dimensional drawing



### Dimensional drawing

# Classifications

# eCl@ss

eCl@ss 4.0	27141210
eCl@ss 4.1	27141210
eCl@ss 5.0	27149110
eCl@ss 5.1	27149110
eCl@ss 6.0	27261210
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

### **ETIM**

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002314
ETIM 5.0	EC002314
ETIM 6.0	EC002314



# Protective covers - HC-B 16-SD-MLT/FS-AL - 1584525

### Classifications

### **UNSPSC**

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712
UNSPSC 12.01	39121712
UNSPSC 13.2	39121421

# UNSPSC 13.2 Approvals Approvals Approvals EAC EX Approvals EAC EAC ENDE AI30.B.01102

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com