

Meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541



SPECIFICATIONS

Properties Surface Resistance Sloughing Test

Recyclability

Typical Values 1 x 10^6 to < 1 x 10^9 ohms Negligible surface damage at 10 cycles ar damage at 200 cycles in Taber Abrasian T

Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test. No conductive particles abrased from surface Complete recyclability of package

Features

- · Trays that can stack and nest together for improved use of space
- Great container for Kanban
- Static dissipative foam bottom provides ESD and shock protection

Foam Electrical Properties: 1 x 10⁵ to < 1 x 10⁸ ohms Foam Thickness: 1/8"

Item No.	Size I.D L x W x D (IN)
<u>37750</u>	18 x 11-3/8 x 1-3/4
<u>37751</u>	22-7/8 x 17-1/4 x 2-3/4

Test Procedures/Method

ANSI/ESD STM11.11 ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load Rockwell International Test Report of January 8, 1992 Rockwell International Test Report of January 8, 1992



Unless otherwise noted, tolerance is ±10% Specifications and procedures subject to change without notice.	TEK-TRAYS		
PROTEKTIVE PAK	PROTEKTIVE PAK 13520 MONTE VISTA AVENUE CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 ProtektivePak.com	DRAWING NUMBER 37750	DATE: March 2015

© 2015 DESCO INDUSTRIES INC Employee Owned