## Thermal Transfer Printers

# TT230SM/TT230SMC Thermal Transfer Printers

HellermannTyton's TT230SM and TT230SMC thermal transfer printers are the next generation of printer for small to medium volume users looking for an easy-to-use and functional thermal transfer printer. TT230SM series printers print on a wide variety of materials including all HellermannTyton labels and ShrinkTrak. TT230SM series printers are also Ethernet network ready, which gives the user options on placing the unit away from the host computer. Each printer comes with a label "caddy" that holds large label rolls behind the printer, for easier dispensing and printing. There is also an optional carrying case that can be used to safely transport the printer to remote job sites. The TT230SMC model includes an integrated cutter for use with continuous vinyl label rolls.



- 300dpi thermal transfer print head
- Print speed up to 3" (76.2 mm) per second
- Integrated cutter TT230SMC only
- 2mb flash / 8mb SDRAM
- Easy set up and loading without adjustments
- Label holder included with purchase
- · Highly accurate, adjustable gap sensor
- Low calibration waste
- No complicated settings
- · Lightweight / minimal footprint
- Approvals: CE, FCC, Class A, cULus, UL, GS, TUV-GS, LCC, C-Tick, BSMI, RoHS

#### **Printing Specifications:**

- Prints on ShrinkTrak, continuous vinyl rolls, foam nameplate labels, adhesive labels, TipTags and self laminating labels
- TT230SMC printer with cutter is not recommended for use with ShrinkTrak or foam nameplate labels.
- Uses standard 1/2" core HellermannTyton ribbons: (TT100OUTSM, TT822OUTSM, TTDTHOUTSM, TTHSTOUTSM, TT900OUTSM)
- Maximum print width 4.17" (106 mm)
- Minimum print width 1.0" (25.4 mm)



#### **Specifications**

Dimensions of printer

Weight Power supply

Operation temperature

Print density

Media diameter

Material thickness Operating system Width – 7.95" (201 mm) Height – 6.81" (172 mm)

Depth – 10.16" (258 mm)

5.2 lbs (2.36kg)

100 - 240V

+50°F - +95°F (+10°C - +35°C)

300 dpi

Total diameter – 8.27" (210 mm) Core diameter – 3.0" (76.2 mm) Winding direction – Inside or Outside

.0028" - .007" (.06 mm - .19 mm)

Windows 2000/XP/Vista/7/8



## Thermal Transfer Printers

#### **Communications:**

- RS-232C
- USB 2.0
- Centronics
- Built-in Ethernet



#### **Product Selection**

| Article No: | Part No:  | Type:        | Description:                 | Pkg Qty: |
|-------------|-----------|--------------|------------------------------|----------|
| 556-00230   | 556-00230 | TT230SM      | TT230SM Printer              | 1        |
| 556-00240   | 556-00240 | TT230SMC     | TT230SMC Printer with Cutter | 1        |
| 556-00231   | 556-00231 | CASE 230SM   | Optional Carrying Case       | 1        |
| 556-00232   | 556-00232 | RPH TT230SM  | Replacement Print Head       | 1        |
| 556-00233   | 556-00233 | RPS TT230SM  | Replacement Power Supply     | 1        |
| 556-00234   | 556-00234 | RPR TT230SM  | Replacement Platen Roller    | 1        |
| 556-00235   | 556-00235 | LABEL HOLDER | Replacement Label Holder     | 1        |

#### Labels for TT230SM/TT230SMC Printer

To obtain information on HellermannTyton's selection of labels, view or order a product catalog by visiting **www.hellermann.tyton.com/literature.asp**.



### **TagPrint**®PRO Professional Label Creation Software

- Beginners can use the built-in label design wizard to step through the entire label design process.
- TagPrint Pro allows the user to place graphics, text, bar codes, and lines anywhere on the label.
- All HellermannTyton label sizes are loaded in the software for easy design and printing.



## **HellermannTyton**

## HellermannTyton North American Corporate Headquarters

7930 N. Faulkner Rd, PO Box 245017 Milwaukee, WI 53224-9517 Phone: (414) 355-1130, (800) 537-1512 Fax: (414) 355-7341, (800) 848-9866 email: corp@htamericas.com

www.hellermann.tyton.com

TS16949, ISO 9001, and ISO 14001 Certified

#### HellermannTyton Canada

Unit #4, 205 Industrial Parkway North Aurora, Ontario L4G 4C4 Canada Phone: (800) 661-2461 Fax: (800) 390-3904

email: sales@hellermanntyton.ca

#### HellermannTyton Mexico

Anillo Periferico Sur 7980 Edificio 6A Parque Industrial Tecnologico II Santa Maria Tequepexpan Tlaquepaque, Jalisco, Mexico 45601 Phone: 011-52-33-3-133-9880 Fax: 011-52-33-3-133-9861 email: info@hellermanntyton.com.mx

ISO 9001 Certified

Warranty Policy HellermannTyton products are warranted to be free from defects in material and workmanship at the time sold by us; but our obligation under this warranty and that of the seller is limited to the replacement of the product, and neither we nor the seller are bound by any other warranty, expressed, implied or statutory. Under no circumstances are we or the seller liable for any loss, damage, expenses or consequential damages of any kind arising out of the use or inability to use these products. All are sold with the understanding that the user will test them in actual use and determine their adaptability for the intended uses.