


**OptiMOS™ P3 Small-Signal-Transistor**
**Features**

- Dual P-channel
- Enhancement mode
- Logic level (4.5V rated)
- ESD protected
- Qualified according to AEC Q101
- 100% Lead-free; RoHS compliant


**Product Summary**

$V_{DS}$	-30	V
$R_{DS(on),max}$	$V_{GS}=-10\text{ V}$	80
	$V_{GS}=-4.5\text{ V}$	130
$I_D$	-2.0	A



Type	Package	Tape and Reel Information	Marking	Lead Free	Packing
BSL308PE	PG-TSOP-6	L6327: 3000 pcs/ reel	sPR	Yes	Non dry

**Maximum ratings, at  $T_j=25\text{ °C}$ , unless otherwise specified**

Parameter <sup>1)</sup>	Symbol	Conditions	Value	Unit
Continuous drain current	$I_D$	$T_A=25\text{ °C}$	-2.0	A
		$T_A=70\text{ °C}$	-1.6	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ °C}$	-8.0	
Avalanche energy, single pulse	$E_{AS}$	$I_D=-2\text{ A}, R_{GS}=25\text{ Ω}$	-10.7	mJ
Reverse diode dv/dt	dv/dt	$I_D=-2\text{ A}, V_{DS}=-16\text{ V}, di/dt=-200\text{ A/μs}, T_{j,max}=150\text{ °C}$	6	kV/μs
Gate source voltage	$V_{GS}$		$\pm 20$	V
Power dissipation <sup>2)</sup>	$P_{tot}$	$T_A=25\text{ °C}$	0.5	W
Operating and storage temperature	$T_j, T_{stg}$		-55 ... 150	°C
ESD Class		JESD22-A114 -HBM	2 (2kV to 4kV)	
Soldering Temperature			260 °C	°C
IEC climatic category; DIN IEC 68-1			55/150/56	°C

<sup>1)</sup> Only one of both transistors in operation

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
<b>Thermal characteristics</b>						
Thermal resistance, junction - ambient	$R_{\text{thJA}}$	minimal footprint <sup>2)</sup>	-	-	250	K/W
<b>Electrical characteristics</b> , at $T_j=25^\circ\text{C}$ , unless otherwise specified						
<b>Static characteristics</b>						
Drain-source breakdown voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_D=-250\mu\text{A}$	-30	-	-	V
Gate threshold voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_D=-11\mu\text{A}$	-2.0	-1.5	-1.0	
Drain-source leakage current	$I_{\text{DSS}}$	$V_{\text{DS}}=-30\text{V}, V_{\text{GS}}=0\text{V}, T_j=25^\circ\text{C}$	-	-	-1	$\mu\text{A}$
		$V_{\text{DS}}=-30\text{V}, V_{\text{GS}}=0\text{V}, T_j=150^\circ\text{C}$	-	-	-100	
Gate-source leakage current	$I_{\text{GSS}}$	$V_{\text{GS}}=-20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	-5	$\mu\text{A}$
Drain-source on-state resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}}=-4.5\text{ V}, I_D=-1.7\text{ A}$	-	88	130	$\text{m}\Omega$
		$V_{\text{GS}}=-10\text{ V}, I_D=-2\text{ A}$	-	62	80	
Transconductance	$g_{\text{fs}}$	$ V_{\text{DS}} >2 I_D R_{\text{DS}(\text{on})\text{max}}, I_D=-1.6\text{ A}$		4.6	-	S

<sup>2)</sup> Performed on 40mm<sup>2</sup> FR4 PCB. The traces are 1mm wide, 70µm thick and 20mm long; they are present on both sides of the PCB.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic characteristics**

Input capacitance	$C_{iss}$	$V_{GS}=0 \text{ V},$ $V_{DS}=-15 \text{ V}, f=1 \text{ MHz}$	-	376	500	pF
Output capacitance	$C_{oss}$		-	196	261	
Reverse transfer capacitance	$C_{rss}$		-	12	18	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=-15V,$ $V_{GS}=-10 \text{ V},$ $I_D=-2 \text{ A}, R_G=6 \Omega$	-	5.6	-	ns
Rise time	$t_r$		-	7.7	-	
Turn-off delay time	$t_{d(off)}$		-	15.3	-	
Fall time	$t_f$		-	2.8	-	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=-15 \text{ V}, I_D=-2 \text{ A},$ $V_{GS}=0 \text{ to } -10 \text{ V}$	-	-1.2	-	nC
Gate to drain charge	$Q_{gd}$		-	-0.6	-	
Gate charge total	$Q_g$		-	-5.0	-	
Gate plateau voltage	$V_{plateau}$		-	-3.1	-	

**Reverse Diode**


Diode continuous forward current	$I_s$	$T_A=25 \text{ }^\circ\text{C}$	-	-	-0.4	A
Diode pulse current	$I_{s,pulse}$		-	-	-8.4	
Diode forward voltage	$V_{SD}$	$V_{GS}=0 \text{ V}, I_F=-2 \text{ A},$ $T_j=25 \text{ }^\circ\text{C}$	-	-0.8	-1.1	V
Reverse recovery time	$t_{rr}$	$V_R=-10 \text{ V}, I_F=-2 \text{ A},$ $di_F/dt=100 \text{ A}/\mu\text{s}$	-	14	-	ns
Reverse recovery charge	$Q_{rr}$		-	-5.9	-	

**1 Power dissipation**

$$P_{\text{tot}} = f(T_A)$$



**2 Drain current**

$$I_D = f(T_A); V_{GS} \geq -10 \text{ V}$$


**3 Safe operating area**


$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$





parameter:  $t_p$



**4 Max. transient thermal impedance**



$$Z_{\text{thJA}} = f(t_p)$$


parameter:  $D = t_p/T$





**5 Typ. output characteristics**
 $I_D = f(V_{DS})$ ;  $T_j = 25^\circ\text{C}$ 
parameter:  $V_{GS}$ 
**6 Typ. drain-source on resistance**
 $R_{DS(on)} = f(I_D)$ ;  $T_j = 25^\circ\text{C}$ 
parameter:  $V_{GS}$ 
**7 Typ. transfer characteristics**
 $I_D = f(V_{GS})$ ;  $|V_{DS}| > 2|I_D|R_{DS(on)max}$ 

**8 Typ. forward transconductance**
 $g_{fs} = f(I_D)$ ;  $T_j = 25^\circ\text{C}$ 




**9 Drain-source on-state resistance**
 $R_{DS(on)} = f(T_j); I_D = -2 \text{ A}; V_{GS} = -10 \text{ V}$ 

**10 Typ. gate threshold voltage**
 $V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 11 \mu\text{A}$ 

 parameter:  $I_D$ 

**11 Typ. capacitances**
 $C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}; T_j = 25^\circ\text{C}$ 

**12 Forward characteristics of reverse diode**
 $I_F = f(V_{SD})$ 

 parameter:  $T_j$ 



**13 Avalanche characteristics**
 $I_{AV} = f(t_{AV})$ ;  $R_{GS} = 25 \Omega$ 

parameter:  $T_{j(\text{start})}$ 

**15 Drain-source breakdown voltage**
 $V_{BR(DSS)} = f(T_j)$ ;  $I_D = 250 \mu\text{A}$ 

**14 Typ. gate charge**
 $V_{GS} = f(Q_{\text{gate}})$ ;  $I_D = -2 \text{ A pulsed}$ 


parameter:  $V_{DD}$ 

**16 Gate charge waveforms**


## TSOP-6

### Package Outline:




### Footprint:



Remark: Wave soldering possible dep.  
on customers process conditions

HLG09283

### Packaging:





Published by  
Infineon Technologies AG  
81726 Munich, Germany  
© 2009 Infineon Technologies AG  
All Rights Reserved.

### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.