


Part Number: 5542FE



Security & Sound, #22-3pr, BC, Shielded, CMR

Product Description

Security & Sound Cable, Riser-CMR, 3-22 AWG stranded bare copper pairs with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Pairs |
|-------|--------------|------------------|--------------|
| 22 | 7x30 | BC - Bare Copper | 3 |
| Condu | uctor Count: | | 6 |
| Condu | uctor Size: | | 22 AWG |

Insulation

| Material | Nominal Wall Thickness |
|--------------------|------------------------|
| PP - Polypropylene | 0.007 in |

Color Chart

| Number | Color |
|--------|---------------|
| 1 | Black & Red |
| 2 | Black & White |
| 3 | Black & Green |

Outer Shield Material

| Material | Material Trade Name | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|--------------------|---------------------|--------------------|---------------|------------------------------|
| Aluminum/Polyester | Beldfoil® | TC - Tinned Copper | 24 | Solid |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.201 in | 0.017 in |

Construction and Dimensions

Print Legend: NEW GENERATION(R) BY BELDEN-M 5542FE CMR 75C 3PR22 SHIELDED (UL) E108998 OR C(UL) CMG (2 FT., 7 DIGIT SEQUENTIAL) FEET

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 16.3 Ohm/1000ft | 13.9 Ohm/1000ft |

Capacitance

| | Nom. Capacitance Conductor to Conduct | Nom. Capacitance Conductor to Other Conductor to Shield |
|--------------------------------------|---------------------------------------|---------------------------------------------------------|
| | 24 pF/ft | 43.25 pF/ft |
| Shielding: Foil(s) or Copper Tape(s) | | |

Current

Max. Recommended Current [A]

2 Amps per conductor @ 25°C A

Voltage



Temperature Range

| Operating Temp Range: | -20°C To +75°C |
|-----------------------|----------------|

Mechanical Characteristics

| Bulk Cable Weight: | 22 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 60.1 lbs |
| Min Bend Radius/Minor Axis: | 2 in |

Standards

| NEC/(UL) Specification: | CMR |
|--------------------------|-----|
| CEC/C(UL) Specification: | CMG |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | UL1666 Riser |
|--------------------|--------------|
| CSA Flammability: | FT4 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|----------------|--------|
| Plenum Number: | 6542FE |

Part Number

Variants

| Item # | Color |
|-----------------|-------|
| 5542FE 0081000 | Gray |
| 5542FE 008U1000 | Gray |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.